

Bluestone - Polished

Pre-Grouting Sealing

Purpose To protect porous surface from grout staining and ease grout cleanup.

| Desired Look and Finish | Level of Stain Resistance | Product Options | # Coats | Approx. Coverage per coat per 4 L | Cure Time Prior to Grouting | Notes |
|---------------------------|---------------------------|---------------------------|---------|-----------------------------------|-----------------------------|---|
| Natural Look, No Sheen | Maximum | Aqua-Seal Gold+™ | 1 | 80-100m ² | 2 hours | Recommended in food areas or where maximum stain protection is required. |
| Natural Look, No Sheen | Excellent | ProSeal+™ | 1 | 80-100m ² | 2 hours | Provides limited protection in food areas. Use where excellent stain protection is required. |
| Natural Look, No Sheen | Good | Aqua-Seal Bronze+™ | 1 | 80-100m ² | 2 hours | Provides limited protection in food areas. Use where good stain protection is required. |
| Colour Enhanced, No Sheen | Maximum | Enhance'N'Seal™ | 1 | 80-100m ² | 24 hours | Use only on unsealed surface for darkened color enhancement and seal. |

Note The product selected for pre-grouting sealing should also be used for sealing.

Sealing

Purpose To protect porous surface from staining and ease ongoing maintenance.

| Desired Look and Finish | Level of Stain Resistance | Product Options | # Coats | Approx. Coverage per coat per 4 L | Grout Cure Time Prior to Sealing | Notes |
|---------------------------|---------------------------|---------------------------|---------|-----------------------------------|----------------------------------|--|
| Natural Look, No Sheen | Maximum | Aqua-Seal Gold+™ | 2 | 100-120m ² | 48 hours | Recommended in food areas or where maximum stain protection is required. |
| Natural Look, No Sheen | Excellent | ProSeal+™ | 2 | 100-120m ² | 48 hours | Provides limited protection in food areas. Use where standard stain protection is required. |
| Natural Look, No Sheen | Good | Aqua-Seal Bronze+™ | 2 | 100-120m ² | 48 hours | Provides limited protection in food areas. Use where basic stain protection is required. |
| Colour Enhanced, No Sheen | Maximum | Enhance'N'Seal™ | 2 | 100-120m ² | 48 hours | Use only on unsealed surface for darkened color enhancement and seal. |

Maintenance

Purpose To safely maintain a clean surface and to preserve it's beauty and integrity.

| Type of Maintenance | Product | Dilute as per label instructions - refer to product Technical Data Sheet | Approx. Coverage per 4 L | Notes |
|--|-----------------------|---|------------------------------------|---|
| Routine | EzyClean™ | 10-30 ml per 4 litres water | 1,000-2,000m ² | Highly-concentrated. Neutral pH. Safe for regular use. |
| Periodic Heavy-Duty | XtremeClean™ | Light: Mix 1:10 parts water Moderate: Mix 1:5 parts water Heavy: Mix 1:3 parts water | 40-130m ² | Contains no acid. Safe on stone & grout. Will remove wax-type finishes. |
| Periodic Heavy-Duty Large Commercial Areas | DeepClean Pro™ | Regular: 30g powder & 60ml of liquid Heavy: 60gm powder & 120ml of liquid | 1,000-3,200m ² per unit | Recommended for large commercial areas. Will remove wax-type finishes. |
| Antibacterial Cleaner | VeriClean™ | Use undiluted | N/A | Antibacterial spray and wipe cleaner. |
| Routine - Counter Top | Clean'N'Gleam™ | Use undiluted | N/A | Spray and wipe cleaner for all polished non-traffic areas. |
| Routine - Counter Top | Glow™ | Use undiluted | N/A | Counter, bench or table top polish for polished surfaces. |

These recommendations are intended as general guidelines for pre-grout sealing, sealing and maintenance. Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents. For Architectural specifications please contact Aqua-Seal STC™