

# PS14 - Remove Sealer Residue

Remove Sealer Residue from all Natural Stone, Porcelain and Encaustic Tiles

**PRODUCT:**      **MICROSCRUB**



**EQUIPMENT:**

<ul style="list-style-type: none"> <li>• <u>AQUABUG CLEANING KIT;</u></li> <li>• Scrub pad or brush;</li> <li>• Broom</li> <li>• Bucket</li> </ul>	<ul style="list-style-type: none"> <li>• Clean water;</li> <li>• Cotton towels.</li> <li>• Wet vac;</li> <li>• Optional: Scrub machine</li> </ul>
--	---

**PRECAUTIONS:**

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection;
3. Use when surface temperature is between 4°C & 32°C;
4. Do not allow product to contact any non-recommended surfaces;
5. Take care when using on dark coloured grout or stone;

**PROCEDURE:**

1. Sweep, vacuum, or wipe surface;
2. Slightly pre-wet surface & grout joints with clean water;
3. Pour approx 1-2 cups of **MICROSCRUB** to the pre wet surface;
4. Scrub the surface with a white nylon pad, scrub brush or scrub machine;
5. For vertical surfaces, pre-wet surface by spraying water from a spray bottle then apply **MICROSCRUB** directly to a white nylon pad then scrub;
6. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
7. Remove the dirty solution with a wet vac or mop;
8. Rinse thoroughly with clean water;
9. Repeat as necessary.

**Note A:** **MICROSCRUB** does not affect the performance of natural look, penetrating sealers as it will only remove the surface residue;  
**Note B:** For extreme heavy sealer residue, use **STRIP-IT** as per label instructions. You must then re-apply sealer as per label instructions.;

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

**READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES**