

## Marble - Honed

Marble is a granular metamorphic rock composed of recrystallized carbonate minerals, most commonly calcite or dolomite. Recrystallisation is caused by metamorphism (heat and pressure) of these minerals. This also results in the different type of veining and colours seen in marble along with the different textures (fine to coarse). A honed finish is smooth with little or no gloss (flat or satin finish). Due to the high content of calcium carbonate, travertine is susceptible to etching from acid based contaminants eg wine, citrus, soft drinks etc

### Pre-Sealing

**Purpose:** To protect porous surface from staining and ease grout clean up during installation.

Pre-Sealing Options	Product Name	# Coats	Coverage Per 4 litres Per Coat*	Important Notes
Six Sided / Dip Sealing	<b>Ultra-Block</b>	1	15 m <sup>2</sup>	When a six sided sealing process is desired to help minimise efflorescence, mineral blooming and picture framing.
Surface Pre-Sealing when dark or contrasting grout is used	<b>Grout Release Pro</b>	1	60 m <sup>2</sup>	To be used when a dark or contrasting grout is used. Apply <b>AFTER</b> the initial coat of <b>Ultra-Block, Aqua-Seal Gold+</b> or <b>Enhance'N'Seal</b> has cured & before starting the grouting.
Surface Pre-Sealing for a Natural Look	<b>Aqua-Seal Gold+</b>	1	60 - 80 m <sup>2</sup>	Only for a NATURAL look. To pre-seal the top surface only. Helps with the grouting clean up process. Helps minimise staining from handling & adhesives during the installation
Surface Pre-Sealing for a Colour Enhanced Look	<b>Enhance'N'Seal</b>	1	60 - 80 m <sup>2</sup>	Only for an ENHANCED look. To pre-seal the top surface only. Helps with the grouting clean up process. Helps minimise staining from handling & adhesives during the installation

**Note:** Use **Haze Away** as per label instructions to further help grout clean-up process and minimise grout haze.

### Sealing

**Purpose:** To help protect porous surface from staining and ease ongoing maintenance.

Desired Look	Stain Resistance	Product Name	# Coats	Coverage Per 4 litres Per Coat*	Important Notes
Natural Look	<b>Best</b>	<b>Aqua-Seal Gold+</b>	2	80 - 100 m <sup>2</sup>	Best recommendation for a natural look & maximum stain resistance. Ideal for residential, commercial, high traffic and also for food areas. Will also seal surrounding porous grout.
Natural Look (Small Areas)	<b>Best</b>	<b>Spray'N'Seal</b>	2	10 - 15 m <sup>2</sup> (Per 450ml can)	Best recommendation for small areas. For a natural look & maximum stain resistance. Ideal for residential, commercial, high traffic & also for food areas. Will also seal porous grout.
Colour Enhanced Look	<b>Best</b>	<b>Enhance'N'Seal</b>	2	80 - 100 m <sup>2</sup>	Best recommendation for a colour enhanced/darkened look & maximum stain resistance is required. Ideal for residential, commercial, high traffic & also for food areas. Will also seal & enhance porous grout. Enhancement cannot be reversed.

**Note:** Sealers are not waterproofing agents and do not protect against etching by acid based contaminants or harsh chemicals.

### Maintenance

**Purpose:** To safely clean & maintain the surface and to preserve it's beauty & integrity.

Type of Maintenance	Product Name	Important Notes
Regular Cleaning	<b>EzyClean</b>	Highly-concentrated. Neutral pH. Safe for everyday/regular use. Will not affect sealers, stone, tile or grout. Rinse free, streak free formula. Fresh lemon scent.
Heavy Duty Cleaning	<b>XtremeClean</b>	Heavy duty cleaner & degreaser. Safe on natural stone, encaustics, tiles & grout. Use on heavily soiled and neglected areas. Ideal as a periodic heavy duty cleaner.
Cleaning & Re-Sealing - Tops	<b>AquaGuard</b>	Spray and wipe, one step cleaner & re-sealer. Use on sealed surfaces to prolong the performance of existing sealer. Cleans off dirt, grease & grime. Safe for food areas.
Cleaning & Deodorising - Tops	<b>Clean'N'Gleam</b>	Spray and wipe cleaner and deodoriser. Use on natural stone and engineered stone surfaces. Safe for food areas. Cleans off dirt, grease and grime.

**Note:** Do not use abrasive or acid based products.

These recommendations are intended as general guidelines for sealing and maintenance. Read product label, technical bulletin & SDS thoroughly prior to use. Always test first. Keep floors dry to prevent slip falls.  
\* All Coverages are approximate and only as a guide. Coverage will vary depending on surface density, porosity, texture and absorption. Also weather conditions, the application method and number of coats.