

# AquaShield GT™

## Premium Glass & Shower Tile Sealer



### DESCRIPTION & USE

AquaShield GT™ utilises the latest Nano-AQS™ Coating Technology to provide excellent protection against build up of soap scum, dirt, hard water & lime scaling. **USE:** On all glass surfaces including Shower Screens, Glass Splashbacks, Mirrors, Outdoor Windows, Automotive Windshields, Glass Roofs etc. For indoor, outdoor, domestic & commercial areas. (**NOT for floor use.**)

### TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

### PRECAUTIONS & SAFETY DIRECTIONS

1. Always test first;
2. Read entire label, SDS & product technical bulletin before using;
3. Wear appropriate skin and eye protection & use in a well ventilated area;
4. Surface must be clean, dry and free from any sealers & coatings;
5. Use when surface temperature is between 4°C & 25°C;
6. Do **NOT** use on floor area or allow to settle on floor as floor will become slippery.

### PREPARATION

Use below products as per label instructions:

- ▶ For new glass: Use XtremeClean™.
- ▶ For existing glass: Use XtremeClean™ or OxiTreat HD™ depending on severity of dirt or soap scum;

### APPLICATION INSTRUCTIONS:

1. Clean & wipe surface **COMPLETELY** dry;
2. Spray AquaShield GT™ liberally to the glass or mirror surface;
3. Using a clean dry absorbent cloth, work in a circular motion and cover the whole glass area overlapping the motion as you go.
4. Allow the film to dry (approx 3-5 minutes);
5. When dry, polish off residue **COMPLETELY** with a new clean dry absorbent cloth;
6. Keep dry for minimum 1 hour.

### LIMITATIONS

- ▶ Sealer will not prevent surface wear or etching from harsh or acidic chemicals
- ▶ Sealer is **NOT** a waterproofing agent.

### EXPECTED WEAR

Will vary depending on surface wear plus frequency & type of maintenance products used. Harsh cleaning methods, pressure washing, high alkaline, acidic or solvent-based cleaners or weather exposure will affect wear and performance. Exterior & high use may require more frequent applications. RE-SEAL AS NECESSARY

### MAINTENANCE

- ▶ EzyClean™ for routine, everyday cleaning;
- ▶ XtremeClean™ for heavy duty cleaning;

### HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use.
- ▶ Store between 4°C and 32°C.
- ▶ Do not re-use container. Discard in rubbish.
- ▶ Clean tools with solvent before product dries

### FIRST AID

Contact a doctor or Poisons Information Centre (Aust 13 11 26, NZ 0800 764 766). Skin & Eye Contact: Irritation is unlikely. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed. Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Ingestion: If swallowed, do **NOT** induce vomiting. Wash mouth with water & give some water to drink. General: In case of accident or if you feel unwell, seek medical advice immediately.

### SAFETY DIRECTIONS

- ▶ Wear protective gloves, eye & skin protection when using.

### PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**