

# Poultice Powder™

## Stain Removing Powder



### DESCRIPTION & USE

**DESCRIPTION:** **Poultice Powder™** is a highly effective, easy to use, non acidic, absorptive clay powder designed to help remove most deep set stains from porous surfaces. It can also to be used as a mild abrasive cleaner to help boost the performance of cleaners for stubborn areas and remove light grout haze from natural stone. **USE:** On porcelain tiles, natural stone, terracotta, masonry and other porous surfaces.

### TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

### PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & product technical bulletin before using;
2. Wear appropriate gloves, skin & eye protection and use in a well ventilated area or use an appropriate mask;
3. Use when surface temperature is between 4°C and 32°C.
4. Do not allow product to come in contact with any non-recommended surfaces;
5. Some soft polished natural stones may dull if a harsh abrasive action or a high RPM scrubber is used.

### INSTRUCTIONS:

1. Sweep, vacuum, or wipe surface;
2. Mix **Poultice Powder™** with water to form a thick paste to a toothpaste consistency;
3. Apply 6mm of paste in a uniform coat over stained area (cover an area slightly larger than actual stain);
4. Cover with foil or plastic wrap and tape down borders with glue residue free tape;
5. Poke a few holes in the surface of the foil or plastic wrap;
6. Allow paste to remain covered until it dries - this may take 24-48 hours or longer, depending on conditions;
7. When dry, remove paste from the surface with a plastic spatula;
8. Rinse thoroughly with clean water to remove any residue;
9. Repeat as necessary.

### IMPORTANT NOTE

Depending on the type of stain or its severity, replace water with the appropriate **Aqua-Seal STS Cleaner** or **Problem Solver** product - refer to Stain Removal Guide at [www.aqua-seal.com.au](http://www.aqua-seal.com.au)

### COVERAGE

The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

### HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use;
- ▶ Store in original container between 4°C and 32°C;
- ▶ Do not re-use empty container. Discard in rubbish or recycle.
- ▶ Wash tools, gloves & shoes thoroughly with clean water;

### FIRST AID

Contact a doctor or Poisons Information Centre (Australia Ph: 131-126, NZ Ph: 0800 764766). If swallowed, do NOT Induce vomiting. Immediately give at least 3-4 glasses of water. If In eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If Irritation persists, seek medical attention.

### SAFETY PRECUATIONS

- ▶ Avoid contact with skin & eyes.
- ▶ Do NOT breath dust.

Code	Size	Barcode Number
125-001	1 kg - Poultice Powder	9347177001524

### PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**