

Poultice Plus™

Stain Removing Paste



DESCRIPTION & USE

Poultice Plus™ is a non flammable, non toxic, and easy to use pre-mixed poultice paste to remove most stains. Safe on all natural stone, tile, concrete and grout to help remove stains from oil, coffee, tea, red wine etc. **USE:** Stone, grout, concrete, porcelain tile, encaustic tiles and other surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

PRECAUTIONS & SAFETY DIRECTIONS

1. Always test first;
2. Read entire label, SDS & technical bulletin before using;
3. Wear appropriate skin and eye protection.
4. Surface must be clean & completely dry & free from any other sealers & coatings;
5. Use when surface temperature is between 4°C & 32°C

Code	Size	Barcode Number
124-003	300 gm - Poultice Plus	9347177001531

APPLICATION INSTRUCTIONS:

1. Stir well before using as product may settle (mix to a creamy toothpaste consistency. Add a small amount of water if required);
2. Sweep, vacuum, or wipe surface;
3. Apply 6mm thickness of **Poultice Plus™** in a uniform coat over stained area (cover an area slightly larger than actual stain);
4. Cover with foil or plastic wrap and tape down borders with glue residue free tape;
5. Poke a few holes in the surface of the foil or plastic wrap;
6. Allow **Poultice Plus™** to remain covered until it dries - this may take 24-48 hours or longer, depending on conditions;
7. When dry, remove **Poultice Plus™** from the surface with a plastic spatula;
8. Rinse thoroughly with clean water;
9. Repeat as necessary.

NOTE: For large or stubborn areas, use **Poultice Powder** mixed with water or the appropriate Aqua-Seal STS chemical (refer to www.aqua-seal.com.au under **Stain Removal Guide**)

LIMITATIONS

- ▶ The degree of success will be determined by factors including but not limited to type of surface stained, length of time stain has been in place, & whether the surface stained is sealed or unsealed.

COVERAGE

Coverage will vary depending on size and depth of stain, density, porosity, texture, surface absorption, weather conditions and number of times the procedure needs to be repeated.

HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use. Store in original container only.
- ▶ Store and use in temperatures between 4°C and 32°C.
- ▶ Wash hands & clothes with clean water before product dries.

FIRST AID

For advice, contact a Poisons Information Centre (Phone 131 126) or a doctor. If swallowed, do NOT induce vomiting. Immediately give at least 3-4 glasses of water. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons

PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**