

# Renue'N'Seal™

## Premium Grout Colorant



### DESCRIPTION & USE

**Renue'N'Seal™** is a premium grout colorant utilising an AQS™ Modified Waterborne Epoxy formula to renew, re-colour and seal existing grout. Can be used on walls and floors, indoor and outdoor areas and in domestic or commercial applications.  
**USE:** Use on textured, sanded, un-sanded & epoxy grout where a new & uniform consistent colour is desired.

### TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

### PRECAUTIONS & SAFETY DIRECTIONS

1. Read label, SDS & product technical bulletin before using;
2. Wear appropriate skin and eye protection;
3. Ensure that existing grout sits lower than the tile surface;
4. Grout must be textured, clean & COMPLETELY dry and free from any other sealers & coatings;
5. Use when surface temperature is between 4°C & 32°C;
6. When using contrasting colours, more than 1 coat might be necessary with a drying time of 2 hours between each coat. Follow label "Application Instructions" for each coat;
7. If using more than 1 bottle of a single colour, mix all the material to be used together in a large container to ensure uniform colour. Check batch numbers before starting;
8. Textured or porous surfaces require more care when applying colorant. Check for ease of clean-up beforehand;
9. For shower floors, the use of a moisture meter can help determine when the existing grout is **COMPLETELY** dry and ready to apply **Renue'N'Seal**;

### PREPARATION

1. Use **OxiTreat HD™** (for smooth grout to create texture) or **XtremeClean™** (for existing textured grout) as per product label instructions to clean and prepare existing grout;
2. Rinse grout thoroughly then allow to **COMPLETELY** dry.

### APPLICATION INSTRUCTIONS:

1. **SHAKE WELL BEFORE USING;**
2. Existing grout must be textured, clean & **COMPLETELY** dry;
3. Sweep, vacuum, or wipe surface;
4. Apply small amount of product directly onto grout joint;
5. Work the product along the grout joint in a back-forward motion using a Colorant Applicator or a kid size toothbrush;
6. Ensure a thin even coat is applied and minimise the amount spread on to the surrounding tile surface then clean off;
7. Ready for light traffic after 2 hours. Keep dry for a minimum 24 hours. Shower floors ok to use after 24-48 hour cure time.

### CLEAN OFF INSTRUCTIONS:

#### CLEAN UP-METHOD A:

Immediately wipe excess product from tile surface using a slightly damp chamois or sponge. Avoid wiping directly in grout joint.

#### CLEAN UP-METHOD B:

Allow product to dry to the touch (Minimum 15-20 minutes but no longer than 2 hours) then mist a small amount of water on the surface. Using a white nylon pad, remove excess product from the tile surface, ensuring that you do not scrub directly into the grout joint;

### LIMITATIONS

- ▶ Colour swatches on marketing material are only indicative & can vary due to printing & screen resolution;
- ▶ Colour & shade variation can occur depending on batch, job site, lighting, surface and surrounding conditions;

- ▶ Do not use in under water or pooling water situations or areas subject to hydrostatic pressure;
- ▶ **Renue'N'Seal™** is NOT a waterproofing agent.

### EXPECTED WEAR

Will vary depending on surface wear plus frequency and type of maintenance products used. Harsh cleaning methods and/or high-alkaline, acidic, or solvent-based cleaners and weather exposure will affect wear and performance. Shower areas, exterior, high use & high traffic areas may require more frequent applications. **RE-APPLY COLORANT AS NECESSARY.**

### COVERAGE

Full chart at [www.aqua-seal.com.au](http://www.aqua-seal.com.au) The coverage will vary depending on tile size plus joint width, porosity, texture & absorption plus weather conditions, the application method and number of coats.

Tile Size	1.5mm	3mm	5mm
300 x 300	60m <sup>2</sup>	30m <sup>2</sup>	15m <sup>2</sup>
400 x 400	80m <sup>2</sup>	40m <sup>2</sup>	20m <sup>2</sup>
600 x 600	120m <sup>2</sup>	60m <sup>2</sup>	30m <sup>2</sup>

### MAINTENANCE

- ▶ **EzyClean™** for routine, everyday cleaning;
- ▶ **XtremeClean™** for periodic heavy duty cleaning;
- ▶ **Deep Clean Pro™** for large commercial areas;

### HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use
- ▶ Store between 4°C and 32°C.
- ▶ Do not re-use container. Discard in rubbish
- ▶ Shelf life is approximately 2 years in un-opened container. Storage beyond that time does not necessarily mean the product is not usable. Do a small test area first.
- ▶ Clean hands & tools with water before product dries

### FIRST AID

Contact a doctor or Poisons Information Centre (Aust 131-126, NZ 0800 764 766). Eye Contact: If in eyes, hold eyelids apart & flush continuously with running water until advised to stop or for at least 15 minutes. General: In case of accident or if you feel unwell, seek medical advice immediately.

Code	Colour	Code	Colour	Code	Colour
190-001	Black	191-001	Midnight	191-009	Charred Ash
190-002	White	191-002	Slate Grey	192-002	Gunmetal Grey
190-003	Cocoa	191-003	Buff	192-003	Grey
190-004	Linen White	191-004	Misty Grey	192-004	Silver Grey
190-006	Antique White	191-005	Magellan Gray	192-005	Vanilla
190-008	Silver	191-006	Travertine	192-007	Light Grey
190-010	Canvas	191-007	Havanna	192-008	Mocha
190-011	Ultra White	191-008	Alabaster		

### PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**