

# Spray'N'Seal™

## Premium Aerosol Sealer - Natural Look



### DESCRIPTION & USE

Spray'N'Seal™ is a breathable, premium, natural look sealer to provide maximum stain resistance to stone, tile, mosaics, grout & other porous surfaces. It is non-yellowing, non-coating and UV resistant. Can be used on newly installed grout 2 hours after grouting however for best performance allow grout to fully cure before sealing. Utilises the latest Nano-AQS™ & Rapid-Seal C6 Fluoro™ Technology to provide good stain resistance after only 4 hours. Can also be used as a pre-grouting sealer. Allows excellent Moisture Vapour Transmission (MVT). For interior & exterior. **USE:** For Porous Stone, Tile, Grout, Glass, Mosaics, Canvas, Wood etc

### TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

### PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & product technical bulletin before using;
2. Wear appropriate skin & eye protection & use in a well ventilated area or wear a suitable mask;
3. Surface must be clean & completely dry and free from any other sealers & coatings.
4. Use when surface temperature is between 4°C & 32°C.
5. Do not allow contact with any non-recommended surfaces;
6. Do NOT use on underside of tile or stone;
7. May slightly darken some surfaces;

### PRE-GROUT SEALING

1. Allows quick & easy clean-up after grouting as grout may stain surfaces.
2. Do NOT saturate the open grout joints;
3. Allow minimum 4 hours cure time before grouting.
4. Where a dark or contrasting colour is to be used, apply Grout Release Pro™ AFTER a coat of Spray'N'Seal™ has been applied and has cured.

### PREPARATION

Use XtremeClean™ as per label instructions to clean and prepare surface to be sealed.

### APPLICATION INSTRUCTIONS:

1. Sweep, vacuum or wipe surface clean;
2. Shake can well before using;
3. Apply product directly to clean, dry surface from approximately 20-30mm and spray in an even, slow sweeping motion;
4. If only sealing grout joints minimize spray on the surrounding areas;
5. If severe over-spray occurs, wipe the surface DRY with absorbent paper or cotton towels after 5-10 minutes, to remove any excess sealer;
6. If 2 or more coats are required, allow minimum 30 minutes between coats and follow label instructions for each coat;
7. The surface is ready for light traffic after 2 hours;
8. Keep surface dry for minimum 24 hours.

### LIMITATIONS

- ▶ Sealer will not prevent surface wear or etching from harsh or acidic chemicals
- ▶ Sealer is NOT a waterproofing agent.

### EXPECTED WEAR

Lasts up to 15 years with correct maintenance. Will vary depending on surface wear plus frequency & type of maintenance products used. Harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners & weather exposure will affect wear & performance. Exterior, high use & high traffic areas may require more frequent applications. **RE-SEAL AS NECESSARY.**

### COVERAGE

Per coat: Seals up to 750 linear metres of grout depending on size & width of the grout joint. Seals up to 27 square metres of low porosity tile. The more porous the surface the lower the coverage. The coverage will vary depending on density, porosity, texture, surface absorption, weather conditions, the application method and the number of coats required. View full coverage chart at [www.aqua-seal.com.au](http://www.aqua-seal.com.au)

### MAINTENANCE

- ▶ EzyClean™ for routine, everyday cleaning;
- ▶ Boost™ for routine cleaning & help prolong sealer life span;
- ▶ XtremeClean™ for periodic heavy duty cleaning;
- ▶ Deep Clean Pro™ for large commercial areas;

### HANDLING, STORAGE & CLEAN UP

- ▶ PRESSURISED DISPENSER.
- ▶ PROTECT FROM SUNLIGHT & DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C.
- ▶ DO NOT PIERCE OR BURN EVEN WHEN EMPTY.
- ▶ DO NOT RE-USE EMPTY CONTAINER.
- ▶ DISCARD IN RUBBISH OR RECYCLE.

### FIRST AID

For advice, contact Poisons Information Centre (AUST 131 126, NZ 0800 764 766) or a doctor. Ingestion: Do not induce vomiting. Give water or milk to drink. Eyes: Immediately flush eyes with clean, running water for at least 15 minutes & see a doctor. Skin & Hair: Remove contaminated clothing. Immediately wash contaminated skin & hair with plenty of water. Inhalation: Remove victim from exposure to fresh air. Seek medical advice. General: If irritation persists or feeling unwell, seek medical attention. Additional information available on SDS.

**BEWARE** Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**SAFETY DIRECTIONS** Harmful: May cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to skin. Avoid breathing spray & contact with skin and eyes. Do NOT spray directly on naked flame & NO smoking when using. **FLAMMABLE.**

**PROPELLANT: Hydrocarbon.**  
**UN1950 - AEROSOL** Contains: Heptane

**USE IN A WELL VENTILATED AREA OR WEAR APPROPRIATE VENTILATION MASK**

Code	Size	Barcode Number
155-004	450 ml - Spray'N'Seal	9347177001739

### PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**